


LED ROUND Ceiling Downlight (Power & CCT adj.)

LED Power (W) DIP SWITCH	18W / 25W
Mounting	Bracket
Lumen Output (Lm)	4000K - 1980 Lm (MAX) - 18W 4000K - 2750 Lm (MAX) - 25W
Lumen Efficiency	110 Lm/W (MAX)
CCT (K) DIP SWITCH	3000K / 4000K / 6000K
Beam Angle (°)	120°
Power Factor	>0.95
CRI	>85
IP	54
Input (VAC)	220V -230V
Energy Class	E
LED Chip	SMD 2835
LED Brand	Epistar
Number of LED's	/
Housing	White
Driver incl.	Yes
Driver intern/ extern	Intern
Warranty (years)	3
Dimmable (flicker free)	No
Dimensions (mm)	Ø 330 mm x H 48mm
Life time (Hr)	45.000
IK	10



18W 25W	220V - 230V	3000K 4000K 6000K	CE	3
IP54	120°	DIM	RoHS	

ALSO AVAILABLE IN:

18 / 25W with colorchanging
+ motion sensor (time, distance adjust)
+ 3W - 3Hrs Emergency Kit
+ sensor - Emergency Kit

ART. NUBMER:

0260-025-0001
0260-025-0002
0260-025-0003
0260-025-0004